



PRIND	8900701	8900702	8900703	8900704	8900705	8900706	8900707	8900708	8900709	8900766
DN	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3
φ	10	10	14.5	19	24.5	31	39.5	49	64	73
I1	11	11	14	16.5	16.5	18.5	21.5	20.5	27	25
I2	11.5	11	14	16.5	18	18	18.5	20.5	25.5	25
L	45.5	45.5	54	65.5	74	84.5	96.5	110	138.5	150.5
H	38	38	36.5	41	50	55	69.5	80	94.5	104
M	96	96	96	96	132	132	150	178	222	270
PN	40									25

NO.	Part name	Material
1	Body	CW617N
2	Bonnet	CW617N
3	Ball	CW617N
4	PTFE seat	PTFE
5	Stem	CW617N
6	Packing gland	PTFE
7	Packing nut	CW617N
8	Handle	Steel
9	Hex screw cap	Steel

**Technical requirements:**

- 1) Surface: Nickel plated
- 2) PN40 working Temperature: -10°C ~ 100°C,  
PN25 working Temperature: -10°C ~ 80°C
- 3) PN40 max pressure: 40 bar,  
PN25 max pressure: 25 bar
- 4) Threaded ends: ISO 228



GmbH

Code

JL-7501

Description