

The TRIMIG 200-4S is a « synergic » three phase welding unit, ideal for maintenance and locksmith work.

It can weld steel, stainless, aluminium, and it is particularly suitable for intensive professional work up to $\varnothing 1$.

PRODUCT

In « Synergic » mode, setting is fast and simple. The Micro processor controller will automatically set the optimum wire speed. This avoids complex set-up and ensures optimum welding parameters.

3 FUNCTIONS AVAILABLE

- **Normal**
- **Spot:** Spot welding with adjustable spot diameter
- **Delay:** « Chain spot » function (Spot welding with time adjustment between 2 spots).

SYNERGIC MODE FOR EASY AND QUICK SETTINGS

With this function, the wire speed setting is **Automatic**.

- Simply select:
- ✓ the wire type
 - ✓ the wire \varnothing
 - ✓ the power

TRIMIG 200-4S sets the **optimum wire speed** for you.



Ref. 033818

Save the last settings.

Ref. 033818 comes complete with: Trimig 200-4S, 1 torch 250 A of 4m length, 2m earth clamp (Manometer not included).

Ref 041233: **Not included** Torch MB25 kit (250A)



Composition:

- Contact tips:
 - $\varnothing 0,8$ M6 steel/stainless (x 5)
 - $\varnothing 1,0$ M6 steel/stainless (x 5)
 - $\varnothing 1,0$ M6 Alu (x 5)
- Contact tips supports 250A (x 3)
- Springs for nozzle (x 5)
- Nozzles 250A (x 3)

CE EN 60974-1

50/60Hz	AM	min>max	\varnothing mm GAS NO GAS	\varnothing mm 100 200 300	Electronic Control	équipé d'origine original equipment originalausstattung equipamiento de fabrica	EN60974-1 (40°C)	U ₀	cm kg	Protected & compatible POWER GENERATOR (+/-15%)
400V	10A	30 200	0,6 1,0	✓ ✓	✓	0,8/1,0 1,0	140A 200A 30%	17V 34,5V	47x77x79cm 63kg	7,5kVA